



Model		COD. 314430
System		
Main Processor	ARM Cortex A17 Quad-core Processor	
Operating System	Embedded LINUX	
Video		
Input	36 Channel, Support 4096x2160, 2592x1944, 2048x1536, 1920x1080, 1280x960, 1280x720, etc.Incoming Bandwidth: 300MB	
Output	1 VGA, 1 HDMI	
Audio		
Input	1 Port RCA	
Output	1 Port RCA	
Alarm		
Sensor Input	NO	
Output	NO	
Motion Detection	36 Channel	
Email Alarm	Support	
Display		
VGA	Resolution: 1920x1080/1280x1024/1280x720	
HDMI	Resolution:4K 3840x2160/1920x1080/1280x1024/1280x720	
Display Split	36ChxD1/25ChxD1/16ChxD1/9ChxD1/4ChxD1/1Chx1080P/1Chx3MP/1Chx4MP/1Chx5MP/1Chx4k	
Digital Zoom	YES	
OSD	Camera Title, Time, Video Loss, Recording, Motion Detection	
Recording		
Video Compression	H.264/H.265	
Resolution	4k(4096x2160),5MP(2592x1944),4MP(2688x1520),3MP(2048x1536),1080P(1920x1080),960P(1280x960),720P(1280x720),D1 (704x576/704x480)	
Record Rate	PAL: 4k@30x25fp,5MP@36x25fp,4MP@36x25fp,3MP@36x25fp,1080P@36x25fp, 960P@36x25fp, 720P@36x25fp, D1@36x25fp NTSC: 4k@30x30fp,5MP@36x30fp,4MP@36x30fp,3MP@36x30fp,1080P@36x30fp, 960P@36x30fp, 720P@36x30fp, D1@36x30fp	
Record Mode	Manual\Timer\Motion Detection	
Playback & Backup		
Local Sync Playback	4 channelx4k	
Remote Sync Playback	YES	
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection	
Playback Functions	Play, Pause, Stop, Rewind, Fast Play, Slow Play, Digital Zoom	
Backup Mode	USB Device/Network	
Network		
Interface	1 RJ45 10M/100/1000M Adaptive Ethernet Interface	
Network Functions	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, FTP, IP Search, P2P	
Onvif Version	Support Onvif 2.4	
Web Browser	IE6-11, Google Chrome (IE Tab), Firefox (IE Tab)	
CMS Software	Support Windows XP / Windows Vista / Windows 7/ Windows 8	
Cloud Support(P2P)	Yes	
Smart Phone	iPhone, iPad, Android, Android Pad	
Hard Disk Driver		
Interface Type	2 SATA Interface	
Capacity	Up to 12TB capacity	
General		
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek	
USB Interface	2 USB 2.0 Interfaces ,1 USB 3.0 Interface	
Power Supply	DC12V/3A	
Working Environment	-10-55°C/10-90%	
Dimension(WxDxH)	354mmx263mmx50mm	
Weight	4.5KG (without HDD)	