



Model	AS-N0850P
System	
Main Processor	ARM Cortex A9 Processor
Operating System	Embedded LINUX
Video	
Input	8 Channel, Support 1920×1080, 1280×960, 1280×720 ect...
Output	1 VGA, 1 HDMI
Alarm	
Sensor Input	NO
Output	NO
Motion Detection	8 Channel
Email Alarm	Support
Display	
VGA	Resolution: 800×600, 1024×768, 1280×720, 1280×1024, 1920×1080
HDMI	Resolution: 720P(1280×720), 1080P(1920×1080)
Display Split	8 Channel / 6 Channel / 4 Channel / 1Channel
Digital Zoom	YES
OSD	Camera Title, Time, Video Loss, Recording, Motion Detection
Recording	
Video Compression	H.264
Resolution	1080P(1920×1080) / 960P(1280×960) / 720P(1280×720) / D1 (704×576/704×480)
Record Rate	PAL : 1080P@200fps, 960P@200fps, 720P@200fps, D1@200fpsNTSC: 1080P@240fps, 960P@240fps, 720P@240fps, D1@240fps
Record Mode	Manual\Timer\Motion Detection
Playback & Backup	
Local Sync Playback	1x1080P
Remote Sync Playback	YES
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Rewind, Fast Play, Slow Play, Digital Zoom
Backup Mode	USB Device/Network
Network	
Interface	9xRJ45 (10M/100M Adaptive Ethernet Interface)
Network Functions	HTTP, IPv4, TCP/IP, DNS, DHCP, NTP, DDNS
Onvif Version	Support Onvif 2.4
Web Browser	IE6-11, Firefox, Chrome (Under Windows System)
CMS Software	Support Windows XP / Windows Vista / Windows 7/ Windows 8
Cloud Support(P2P)	Yes
POE	8 x Independent 100Mbps POE Network Interfaces
Smart Phone	iPhone, iPad, Android, Android Pad
Hard Disk Driver	
Interface Type	2 SATA Interface
Capacity	Up to 8TB capacity
General	
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian
USB Interface	2 USB 2.0 Interfaces
Power Supply	DC 48V 2500mA
Working Environment	-10-55°C/10-90%
Dimension(W×D×H)	354mm×263mm×50mm
Weight	4.5KG (without HDD)