



<b>Model</b>	<b>AS-N0860TP</b>
<b>System</b>	
Main Processor	ARM Cortex A9 Processor(HI3520D)
Operating System	Embedded LINUX
<b>Video</b>	
Input	8 Channel, Support 1920×1080, 1280×960, 1280×720 ect...
Output	1 VGA, 1 HDMI
<b>Alarm</b>	
Sensor Input	NO
Output	NO
Motion Detection	8 Channel
Email Alarm	Support
<b>Display</b>	
VGA	Resolution: 800×600, 1024×768, 1280×720, 1280×1024, 1920×1080
HDMI	Resolution: 720P(1280×720), 1080P(1920×1080)
Display Split	8 Channel / 6 Channel / 4 Channel / 1Channel
Digital Zoom	YES
OSD	Camera Title, Time, Video Loss, Recording, Motion Detection
<b>Recording</b>	
Video Compression	H.264
Resolution	1080P(1920×1080) / 960P(1280×960) / 720P(1280×720) / D1 (704×576/704×480)
Record Rate	PAL : 1080P@200fps, 960P@200fps, 720P@200fps, D1@200fpsNTSC: 1080P@240fps, 960P@240fps, 720P@240fps, D1@240fps
Record Mode	Manual/Timer/Motion Detection
<b>Playback &amp; Backup</b>	
Local Sync Playback	1x1080P
Remote Sync Playback	YES
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Rewind, Fast Play, Slow Play, Digital Zoom
Backup Mode	USB Device/Network
<b>Network</b>	
Interface	9xRJ45 (10M/100M Adaptive Ethernet Interface)
Network Functions	HTTP, IPv4, TCP/IP, DNS, DHCP, NTP, DDNS
Onvif Version	Support Onvif 2.4
Web Browser	IE6-11, Firefox, Chrome (Under Windows System)
CMS Software	Support Windows XP / Windows Vista / Windows 7 / Windows 8
Cloud Support(P2P)	Yes
POE	8 x Independent 100Mbps POE Network Interfaces
Smart Phone	iPhone, iPad, Android, Android Pad
<b>Hard Disk Driver</b>	
Interface Type	2 SATA Interface
Capacity	Up to 8TB capacity
<b>General</b>	
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian
USB Interface	2 USB 2.0 Interfaces
Power Supply	DC 48V 2500mA
Working Environment	-10~55°C/10~90%
Dimension(W×D×H)	345mm×263mm×50mm
Weight	4.5KG (without HDD)