



MODEL	LS-N2004PDT
System	
Main Processor	ARM Cortex A9 Processor(HI3520D)
Operating System	Embedded LINUX
Video	
Input	9CH (1920x1080, 1280x960, 1280x720, etc), Incoming Bandwidth: 46MB
Output	1 VGA, 1 HDMI
Alarm	
Sensor Input	NO
Output	NO
Motion Detection	9 Channel
Email Alarm	Support
Display	
VGA	Resolution: 1024x768、1280x720、1280x1024
HDMI	Resolution: 1080P(1920x1080) 720P:(1280x720)
Display Split	9 Channel / 4 Channel / 1Channel
Digital Zoom	NO
OSD	Camera title, Time, Video loss, Recording, Motion Detection
Recording	
Video Compression	H.264
Resolution	1080P(1920x1080) / 960P(1280x960) / 720P(1280x720) / D1 (704x576/704x480)
Record Rate	PAL: 1080@225fps, 960P@225fps, 720P@225fps, D1@225fps
Record Mode	Manual\Timer\Motion Detection

Playback & Backup	
Local Sync Playback	1x1080P
Remote Sync Playback	YES
Search Mode	ALL, Channel, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play
Backup Mode	USB Device/Network
Network	
Interface	5 x RJ45 (10M/100M Adaptive Ethernet Interface) – 4PoE 100bps (output < 15.4W cad)
Network Functions	HTTP, TCP/IP, IPv4, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, FTP, IP Search, P2P
Onvif Version	Support Onvif 2.4
Web Browser	IE6-11, Google Chrome (IE Tab), Firefox (IE Tab)
CMS Software	Support Windows XP / Windows Vista / Windows 7/ Windows 8
Cloud Support(P2P)	Yes
Smart Phone	iPhone, iPad, Android, Android PAD
Hard Disk Driver	
Interface Type	1 SATA Interface , 2.5"/3.5" SATA
Capacity	Up to 4TB capacity
General	
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek
USB Interface	2 USB 2.0 Interfaces
Power Supply	DC48V/1250mA
Working Environment	-10~55℃/10~90%
Dimension(W×D×H)	215*215*53mm
Weight	2.0KG (without HDD)