



Model	APH4A10H400
Camera	
Image Sensor	1/3" OmniVision 4MP High-resolution CMOS
Horizontal Resolution	4MP
S/N Ratio	≥52dB
PTZ	
Horizontal Rotation Speed	100°/s
Horizontal Rotation Range	360°
Tilt Rotation Speed	200°/s
Tilt Rotation Range	93°
Auto Flip	Horizontal 180°, Vertical 93°
Ratio Speed	Support
360° Scan	User programmable
360° Scan Speed	01-64speed setting available
A-B Scan	User programmable
A-B Scan Speed	01-64speed setting available
Preset Points	220
Go to Preset Speed	200°/s
Guard Tours	3 groups
Guard Points	Max.16 points, dwell time user selectable
Lens	
Focus Length	5mm-50mm
Focus Control	10X Optical Zoom
Night Vision	
Infrared LED	∅ 16x6PCS
IR Range	50m
Auxiliary Interface	
Communication Protocol	TCP/IP, HTTP, FTP, RTSP Support
P2P	YES, Support QR Code
Baud Rate	2400/4800/9600/19200/38400bps
General	
Operating Temperature	Indoor: 0° - +40° Outdoor: -40° - +60°
Operating Humidity	≤95% Non Condensing
Heater & Blower	Auto temperature control
Auto Control IR LED	PWM
Power	DC12V/4A
Infrared LED	∅ 22x6PCS+ ∅ 16x5PCS
IR Illumination Distance	150M
Power Consumption	≤ 36W
Lightning Protection	Transient voltage 6000V
Dimension	32x32x43(cm)
Weight	7.5kgs