



Model	APH4G18H200
<b>Camera</b>	
Image Sensor	1/2.7" OmniVision Low Illumination 2MP
Horizontal Resolution	1080P
S/N Ratio	>50db
<b>PTZ</b>	
Horizontal Rotation Speed	0.6°-200°/S
Horizontal Rotation Range	360°
Tilt Rotation Speed	3.5°-30°/S
Tilt Rotation Range	90°
Auto Flip	Tilt 180°
Ratio Speed	Support
360° Scan	Support
Park Function	Support
360° Scan Speed	01-64speed setting available
A-B Scan	User programmable
Preset Points	220
Go to Preset Speed	200°/s
Guard Tours	8 groups
Guard Points	Max.32 points, dwell time user selectable
<b>Lens</b>	
Focus Length	4.7mm-84.6mm
Focus Control	18X Optical Zoom
<b>Night Vision</b>	
Infrared LED	∅ 11x2PCS+ ∅ 17x4PCS
IR Range	50m
<b>Network</b>	
Network protocol	IPv4/IPv6,HTTP,HTTPS,802.1x,Qos,FTP,SMTP,UPnP,SNMP,DNS,DDNS,NTP,RTSP,RTP,TCP/IP ,DHCP,PPPoE
Simultaneous view number	Max 6CH
Triple stream	Adopt H.264High profile/M-JPEG dual encoding, triple stream output(2CH H.264+1CHMJPEG)
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
<b>General</b>	
Housing	Metal and Plastic,IP66
Operating Temperature	Indoor: 0°- +40° Outdoor: -20°- +60°
Operating Humidity	≤90% Non Condensing
Heater & Blower	Auto temperature control
DWDR	Support
Auto Control IR LED	PWM
Power	DC12V/2A
Power Consumption	≤20W
Lightning Protection	Transient voltage 3000V
Dimension	22.5x24.5x20(cm)
Weight	3Kgs