



Model	APH7B22H200
<b>Camera</b>	
Image Sensor	1/2.7" OmniVision Low Illumination 2MP CMOS
Horizontal Resolution	1080P
S/N Ratio	>58db
<b>PTZ</b>	
Horizontal Rotation Speed	200°/s
Horizontal Rotation Range	360°
Tilt Rotation Speed	100°/s
Tilt Rotation Range	90°
Auto Flip	Horizontal 180°, Vertical 93°
Ratio Speed	Support
360° Scan	User programmable
360° Scan Speed	01-64speed setting available
A-B Scan	User programmable
A-B Scan Speed	01-64speed setting available
Preset Points	220
Go to Preset Speed	200°/s
Guard Tours	3 groups
Guard Points	Max.16 points, dwell time user selectable
<b>Lens</b>	
Focus Length	3.9mm-85.5mm
Focus Control	22X Optical Zoom
<b>Night Vision</b>	
Infrared LED	⌀ 22x8PCS+ ⌀ 16x6PCS
IR Range	120m
<b>Auxiliary Interface</b>	
Communication Protocol	TCP/IP, HTTP, FTP, RTSP Support
P2P	YES, Support QR Code
Baud Rate	2400/4800/9600/19200/38400bps
<b>General</b>	
Operating Temperature	Indoor: 0°- +40° Outdoor: -40°- +60°
Operating Humidity	≤95% Non Condensing
Heater & Blower	Auto temperature control
Auto Control IR LED	PWM
Power	DC12V/4A
IR Illumination Distance	120M
Power Consumption	≤ 36W
Lightning Protection	Transient voltage 6000V
Dimension	32x32x43(cm)
Weight	7kgs